



TUFF STUFF

Clear Heavy-Duty Concrete & Masonry Sealer

1. Product Description

a. Basic Use: Tuff Stuff is a heavy-duty acrylic concrete and masonry sealer. It is designed for excellent adhesion and long wear on new or old concrete. This product is intended for both interior and exterior use. Tuff Stuff dries to a crystal clear finish and will remain clear.

b. Features & Benefits:

- Resists penetration from oils, unleaded gasoline, chemicals, salts, and water.
- Wears and weathers very well.
- Old concrete surfaces do not require etching before application of Tuff Stuff.
- On vertical surfaces, it will seal out water and protect against degradation from airborne contaminants.
- Tuff Stuff helps keep surfaces clean and reduces staining or alkaline efflorescence.
- Cures to a hard, resilient finish.
- Odor-free and non-combustible.

c. Typical Application: Use Tuff Stuff on vertical and horizontal surfaces where a long wearing, heavy-duty sealer is specified. Common applications are driveways, parking garages, ramps, bridges, sidewalks, hangars, shopping malls, factories, and refineries. Use on concrete or masonry structures, exposed aggregate panels, ribs, split block and brick.

d. Color/Appearance: Sealwall Tuff Stuff dries to a crystal clear finish.

e. Limitations: Do not use Tuff Stuff on glazed tile.

f. Storage: Do not freeze.

2. Packaging

Tuff Stuff is packaged in a 1-quart can, 12/1-quart case, 1-gallon can, 4/1-gallon case, 5-gallon pail, and 55-gallon drum.

3. Coverage

Estimated coverage depends on porosity of the surface. Approximately 350 to 500 square feet per gallon on horizontal surfaces. On vertical surfaces, 150 -500 square feet per gallon.

4. Directions for Use

a. Application: Use a low pressure spray, short-napped roller, or a brush. Do not apply below 50°F (10°C) or to surfaces below 50°F. Allow 3 days after a rain before applying outside. Dry to touch in 15 minutes depending on temperature. Allow 24 hours drying time before permitting traffic. On new concrete or terrazzo, simply broom it clean. They should be allowed to cure for at least 14 days before sealing. Old and dirty concrete or terrazzo should be scrubbed with a detergent before applying. Grease and oil should be removed or they will prevent adhesion.

5. Availability

Tuff Stuff is normally available immediately from your local distributor or it will be shipped within 4 working days upon receipt of order. Please contact your local Sealwall representative or call Sealwall Products directly for more information.

6. Warranty

Tuff Stuff is manufactured in strict accordance with the quality control standards of Sealwall Products. It is guaranteed to perform as indicated on this data sheet when applied by competent applicators.